



Document Solutions

> PRINT > COPY > SCAN > FAX

TASKalfa 7551ci
TASKalfa 6551ci

COLOR
MULTIFUNCTION PRODUCT
FOR A4/A3 FORMAT

A PRODUCTIVE DEVICE FOR PERFECT COLOR PRINTS



Mobile Print



Cloud Connect

Fast, efficient, productive and reliable.

With its optimized image-processing engine, you are guaranteed outstanding color print and image quality. The device has a maximal input capacity of 7,650 sheets and can be combined with a 4,000-sheet finisher to allow it to perfectly handle even the heaviest workload.

- > Up to 75/ 70 pages A4 per minute in Black & white and color*
- > 4 GB RAM + 320 GB or more HDD
- > Standard network and mobile printing as well as color scanning
- > Optional expandable fax functions : Dual fax, Network fax, Internet fax
- > Excellent image quality thanks to advanced color technology
- > Individual paper handling options including booklet and tri-folding
- > Comprehensive security functions including IC card reader
- > Long-life components provide unprecedented efficiency and reliability

*For TASKalfa 7551ci

Main Specifications

Model		TASKalfa 6551ci	TASKalfa 7551ci
Main Function		Copy, Print, Scan, Fax (Optional)	
Writing Method		Semiconductor Laser	
CPU		Freescape QorIQ P1022 (Dual Core) / 1067MHz	
Print Speed (A4)	Simplex (Mono/Color)	65 / 65 cpm	75 / 70 cpm
Scanning Speed (A4, 300dpi)	Simplex (Mono/Color)	120 / 120 ipm	
	Duplex (Mono/Color)	200 / 200 ipm	
Memory/ HDD Capacity		Standard 4 GB RAM + 320 GB HDD	
Warm Up Time		60 seconds or less	
Paper Capacity	Standard	4,150 sheets [2 x 500 sheets (Cassette) + 2 x 1,500 sheets (Cassette) + 150 sheets (MPT)]	
	Maximum	7,650 sheets (Main Unit + PF-780 + PF-740)	
Paper Size	Cassette	Min. A5R - Max. 12" x 18" (304 x 457 mm)	
	MPT	Min. A6R - Max. 12" x 18" (304 x 457 mm) & Banner Print 12" x 48" (304 x 1,220 mm)	
Paper Weight	Cassette	60 to 256 g/m ²	
	MPT	60 to 300 g/m ²	
Duplex Printing		Paper size : A5R 12" x 18"; Paper weight : 60 to 256 g/m ²	
Dimension (W x D x H) (Main Unit)		1,039 mm x 801 mm x 1,347 mm (with Control Panel)	
Power Source/ Weight (Main Unit)		AC 220V - 240V, 50/60 Hz / 190 kg	
Power Consumption (Standard configuration)	Copy/ Print Mode	1,350 W or less	1,470 W or less
	Mono Color	1,480 W or less	1,630 W or less
	Stand-by Mode	300W or less	
Noise (ISO7779/ ISO9296)	Copy/ Print Mode	1.8W or less	
	Stand-by Mode	75dB(A)	
Safety Standards : GS/TUV/CE		58dB(A)	
This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard. RoHs compatibility			
Copy Functions (Standard)			
Copy Size/ Resolution		Max. A3 (Ledger) - Min. A6R / 600 x 600 dpi; 9600 x 600 dpi	
First Copy Time		Mono: 5.4 seconds; Color: 6.2 seconds	Mono: 4.8 seconds; Color: 5.9 seconds
Zoom Ratio	Manual	25% to 400% (1% per Step)	
	Pre-defined	Easy Setting : 5Reduce / 5Enlarge	
Multiple Copy		1 to 9999	
Print Functions (Standard)			
Resolution		600 x 600 dpi; 9600 x 600 dpi level	
PDL		PRESCRIBE, PCL6, KPDL3 (PostScript 3 compatible), XPS, PDF Direct Print	
First Print Out Time (Mono/Color)		5.3 sec / 6.3 sec	4.9 sec / 6.1 sec
Supported Protocol		NetBEUI, IPv6, IPv4, IPX / SPX, IPsec, IPP, IPP over SSL, WSD Print, Apple Bonjour	
Operating System Supported		Windows Server 2003, Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows XP, Windows Vista, Windows 7, Windows 8; Apple Macintosh OS 10.x	
Interface		USB2.0 High Speed x 1; 1000BASE-T / 100BASE-TX / 10BASE-T; USB Host interface (USB Host) x 4	
USB Memory Printing/ Format		Standard TIFF, JPEG, PDF, XPS	
Print Features		Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure print via SSL, Quick Copy, proof and hold, private print, job storage and job management functionality, Airprint	
Scan Functions (Standard)			
Color Selection		Auto Color (Color / Gray); Auto Color (Color / B & W); Full Color; Grayscale; Black & White	
Resolution		600dpi, 400dpi, 300dpi, 200dpi, 200 x 400dpi, 200 x 100dpi	
File Format		TIFF, JPEG, XPS, PDF (MMR / JPG / High-compression PDF), Searchable PDF	
Image Type Mode		Text, Photo, Text + Photo, OCR	
Transmission Type		Scan to SMB; Scan to E-mail; Scan to FTP or FTP over SSL; Scan to USB; TWAIN Scan; WSD Scan; WIA Scan	
Address Storage		2,000 addresses (Common address list), 500 groups (Group address list)	
Fax Functions (Optional)			
Original Size/ Paper Size		Max. A3 (Ledger) - Min. A5 (Statement)	
Coding Method		MMR, MR, MH, JBIG	
Transmission Speed		33.6 / 31.2 / 28.8 / 26.4 / 24.0 / 21.6 / 19.2 / 16.8 / 14.4 / 12.0 / 9.6 / 7.2 / 4.8 / 2.4 kbps	
Memory		Standard : 12MB; Maximum : 120MB (with optional fax memory)	
FAX Features		Opt. Internet-fax, network faxing, rotate transmission, rotate reception, duplex reception, memory reception, FAX BOX, remote diagnostics, dual fax with second fax system	
Options			
Platen Cover		Platen Cover Type E	
Paper Feeder		PF-770 : 3,000 sheets Side Deck (A4 / Letter); PF-780 : 500 sheets Multimedia Side Tray; PF-730 : 500 sheets x 2 Paper Deck; PF-740 : 1,500 sheets x 2 Paper Deck (A4 / Letter)	
Finisher		DF-790 : 4,000 sheets Finisher; PH-7C : Punch Unit; MT-730 : 7 bins Mailbox Sorter; BF-730 : Booklet and Tri-Folding Unit	
Interface		IB-50 : For Additional Network, IB-51 : For Wireless LAN	
Fax System		Fax System (B) / Internet Fax Kit (A)	
Data Security		Data Security Kit (E)	
Document Guard		Printed Document Guard Kit (B)	
Card Authentication		Card Authentication Kit (B) / Card Reader Holder (E)	
Copy Tray		Copy Tray (D)	
Banner Guide		Banner Guide (A)	
Consumables & Maintenance Kit			
Toner Kit		TK-8709 (C / M / Y) : 30,000 pages with 5% A4 coverage / TK-8709 (K) : 70,000 pages with 5% A4 coverage	
Maintenance Kit		MK-8715 (A / B / C / D / E) : 600,000 / 600,000 / 300,000 / 300,000 / 300,000 pages with 5% A4 coverage	
Waste Toner Bottle		WT-861 : 150,000 sheets	
Staple Cartridge		SH-12 for optional DF-790	

